

i€4P

iDPRT

Professional thermal transfer / direct thermal dual-use desktop barcode printer with 100-meter ribbon supported



- Print speed up to 8ips
- The modular design of print head makes the disassembly and assembly easy.
- With the function to automatically identify the printer head with 203dpi and 300dpi and automatically configure the printer without PC settings
- With super large storage, DDR2 RAM 128MB, Flash 8GB
- Support multiple interfaces, USB HOST, serial interface, B-type USB, Ethernet port for standard, Wi-Fi and Bluetooth module for optional
- 2.4-inch color LCD screen with operation keys and USB HOST can easily achieve offline operation
- With free label editing software Bartender to make the label editing convenient and easy
- With various media to meet the demand of wide area
- Cool black housing with clamshell structure, with external paper roll holder optional supported



Model		iE4P
Print spec	Printing Method	Direct thermal/Thermal transfer
	Resolution	203 dpi / 300 dpi
	Printing Speed	8 ips(203 dpi) / 6 ips(300 dpi)
	Max.Printing Width	108 mm(203 dpi) / 106 mm(300 dpi)
	Printing Length	2286 mm(203 dpi) / 1524 mm(300 dpi)
	Protocol	Compatible ZPL-II, EPL2, DPL
Media	Width	25.4 mm ~ 118 mm
	Thickness	60 µm ~ 250 µm
	Roll(OD., Max)	127 mm
Ribbon spec	Type	Wax, Wax/Resin, Resin
	Width	30 mm ~ 110 mm
	Inradius	12.7 mm
	Max.Length	100 m
Font	Resident Fonts	Alphanumeric, Simplified Chinese, Traditional Chinese, Japanese, Korean, 29 International Character Sets
	Download Fonts	Support
Barcode	Linear: UPC-A, UPC-E, EAN128, Codabar, CODE128, CODE39, CODE93, EAN-8, EAN-13, UCC/EAN128, POSTNET, ITF14, HIBC, MSI, Plessey, Telepen, FIM, GS1 DataBar, German Post Code, Planet 11 & 13, Japanese Postnet, Interleaved 2 of 5, Standard 2 of 5, Industrial 2 of 5, Logmars, CODE11	
	2D: CODE49, CODABLOCK, PDF417, Data Matrix, Maxicode, QR Code, MicroPDF471, Aztec	
Sensor	Gap Sensor	Transmissive (Fixed, Dual)
	Black mark Sensor	Reflective (Adjustable, Full-Range)
	Other	Out of paper detection, Ribbon detection, lid detection, Temperature detection, Thermal head
Interfaces	Standard	USB Type B, USB HOST, RS232, Ethernet
	Optional	Wi-Fi and Bluetooth
Cutter	Model	Optional black E4GC External Cutter
	Type	Guillotine Cutter
	Method	Full Cut
Display	2.4-inch Colour TFT LCD Display	
RTC Function	Equipped	
Memory	RAM	128 MB
	Flash	8 GB
Electrical	Input	AC 100~240 V, 50/60 Hz
	Output	DC 24 V, 2.5 A
Environmental	Memory	5 °C ~ 50 °C, humidity 25% ~ 85%, non-condensing
	Operation	-40 °C ~ 60 °C, humidity 10% ~ 90%, non-condensing
Software	Driver	Windows 7/8/8.1/10, Windows Server 2008/2012/2016, Linux, MacOS
	Label Design Software	BarTender 2016 UltraLite
Options & Accessory		Black E4P External label Peeler Module , Black E4GC External Cutter Module , External Label Roll Holder
Dimension (L×W×H, mm)		252×201×181
Weight (Kg)		1.8
Agency Approval		CE EMC(EN 55022 Class B), FCC EMC(Class A), CCC, RoHS

IDPRT Xiamen Hanin Electronic Technology Co.,Ltd.

ADD: 5F, 10# Building, Gaoqi South 12 Road, Aide Industrial Park, Huli District, Xiamen, P.R China

TEL: +86-(0)592-5932525 FAX: +86-(0)592-5885992

WEB: www.idprt.com EMAIL: info@idprt.com

